

Safety Data Sheet

According to U.S.A. Federal Hazcom 2012 and Canadian HPR - WHMIS 2015

1. Identification

1.1. Product identifier

Code **HI700620**
Product name **Electrode Cleaning and Disinfection Solution for Skin Residuals**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Electrode Cleaning Solution for Cosmetics Industry.**

1.3. Details of the supplier of the safety data sheet

Name **Hanna Instruments S.R.L.**
Full address **str. Hanna Nr 1**
District and Country **457260 loc. Nufalau (Salaj) Romania**
Tel. **+40 260607700**
Fax **+40 260607700**

e-mail address of the competent person responsible for the Safety Data Sheet

msds@hanna.ro

Product distribution by:

Hanna Instruments, Inc - 584 Park East Drive, Woonsocket, Rhode Island, USA 02895 - Technical Service Contact Information: +1 8004266287 - e-mail: sds@hannainst.com

1.4. Emergency telephone number

For urgent inquiries refer to

USA Emergency Contact Information: +1 8004249300 - CHEMTREC 24 hours/365 days - International Emergency Contact Information: +1 7035273887 - CHEMTREC 24 hours/365 days

2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Classification and Hazard Statement
Flammable liquid, category 4
Eye irritation, category 2

Combustible liquid.
Causes serious eye irritation.

Hazard pictograms:



Signal words: **Warning**

Hazard statements:

H227 Combustible liquid.
H319 Causes serious eye irritation.

Precautionary statements:

Prevention:

P280 Wear protective gloves / face protection.

Response:

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2. Hazards identification ... / >>

P337+P313

If eye irritation persists: Get medical advice / attention.

Storage:

--

Disposal:

--

2.2. Other hazards

Information not available

3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification

x = Conc. %

Classification:

BUTANOL

CAS 71-36-3 $1 \leq x < 2$

Flammable liquid, category 3 H226, Acute toxicity, category 4 H302, Serious eye damage, category 1 H318, Skin irritation, category 2 H315, Specific target organ toxicity - single exposure, category 3 H335, Specific target organ toxicity - single exposure, category 3 H336

EC 200-751-6
INDEX 603-004-00-6

BENZALKONIUM CHLORIDE

CAS 63449-41-2 $0.1 \leq x < 1$

Acute toxicity, category 4 H302, Acute toxicity, category 4 H312, Skin corrosion, category 1B H314, Serious eye damage, category 1 H318, Hazardous to the aquatic environment, acute toxicity, category 1 H400 M=1

EC 264-151-6
INDEX 612-140-00-5

* There is a batch to batch variation.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

4. First-aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

BUTANOL

Risk of serious damage to eyes. Irritation and corrosion, somnolence, Drowsiness, Cough, Shortness of breath, CNS disorders, cardiovascular disorders, Nausea, Vomiting, inebriation, Dizziness, narcosis, depressed respiration.

BENZALKONIUM CHLORIDE

Irritation and corrosion, Cough, Shortness of breath, Risk of blindness!.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

5. Fire-fighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

5. Fire-fighting measures ... / >>

UNSUITABLE EXTINGUISHING EQUIPMENTNone in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

BUTANOL

Combustible. Vapours are heavier than air and may spread along floors. Forms explosive mixtures with air at elevated temperatures. Development of hazardous combustion gases or vapours possible in the event of fire.

BENZALKONIUM CHLORIDE

Combustible. Vapours are heavier than air and may spread along floors. Development of hazardous combustion gases or vapours possible in the event of fire. Fire may cause evolution of: Hydrogen chloride gas, nitrogen oxides.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

USA	NIOSH-REL	NIOSH publication No. 2005-149, 3th printing, 2007.
USA	OSHA-PEL	Occupational Exposure Limits - Limits for Air Contaminants TABLE Z-1-1910.1000.
USA	CAL/OSHA-PEL	California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits (PELs).
	TLV-ACGIH	ACGIH 2019

BUTANOL

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH	-	61	20			
OSHA	USA	300	100			
CAL/OSHA	USA	150	50			SKIN
NIOSH	USA			150 (C)	50 (C)	SKIN

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations.

HAND PROTECTION

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose limit of use will be defined by the manufacturer (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84, OSHA 29 CFR 1910.134.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	colourless	
Odour	Alcohol	
Odour threshold	Not available	
pH	4.9	
Melting point / freezing point	Not available	
Initial boiling point	> 35 °C	(95 °F)
Boiling range	Not available	
Flash point	63 °C	(145,4 °F)
Evaporation rate	Not available	
Flammability (solid, gas)	Not available	

9. Physical and chemical properties ... / >>

Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	1
Solubility	soluble in water
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	not applicable
Oxidising properties	not applicable

9.2. Other information

Total solids (250°C / 482°F)	1,16 %
------------------------------	--------

10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

BUTANOL

Attacks various types of plastic materials.

BENZALKONIUM CHLORIDE

Attacks carbon steel, copper, aluminium and their alloys.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

BUTANOL

Reacts violently developing heat on contact with: aluminium, strong oxidising agents, strong reducing agents, hydrochloric acid. Forms explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

BUTANOL

Avoid exposure to: sources of heat, naked flames.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

BUTANOL

Acute oral toxicity, Symptoms: Nausea, Vomiting, Risk of aspiration upon vomiting., Pulmonary failure possible after aspiration of vomit - Acute inhalation toxicity, Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages:., damage of respiratory tract - Acute dermal toxicity, Skin irritation, Causes skin irritation - Eye irritation, Causes serious eye damage - Specific target organ toxicity - single exposure, May cause respiratory irritation. May cause drowsiness or dizziness.

11. Toxicological information ... / >>

BENZALKONIUM CHLORIDE

Acute oral toxicity, Symptoms: If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the oesophagus and the stomach. absorption - Acute inhalation toxicity, Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages: damage of respiratory tract - Skin irritation, Mixture causes burns - Eye irritation, Mixture causes serious eye damage. Risk of blindness!

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

BUTANOL

LD50 (Oral)

LD50 (Dermal)

LC50 (Inhalation)

790 mg/kg Rat

3400 mg/kg Rabbit

8000 ppm/4h Rat

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

BENZALKONIUM CHLORIDE

LC50 - for Fish 0.3 mg/l/96h

12.2. Persistence and degradability

BENZALKONIUM CHLORIDE
NOT rapidly degradable

BUTANOL

Solubility in water 1000 - 10000 mg/l
Rapidly degradable

12.3. Bioaccumulative potential

BENZALKONIUM CHLORIDE

Partition coefficient: n-octanol/water 0.9 Log Kow

BUTANOL

Partition coefficient: n-octanol/water 1

BCF 3.16

12.4. Mobility in soil

BUTANOL

Partition coefficient: soil/water 0.388

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

12.6. Other adverse effects

Information not available

13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14. Transport information ... / >>**14.1. UN number**

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**U.S. Federal RegulationsTSCA:

All components are listed on TSCA Inventory.

Clean Air Act Section 112(b):

107-21-1 ETHANEDIOL

Clean Air Act Section 602 Class I Substances:

No component(s) listed.

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

Clean Water Act – Priority Pollutants:

No component(s) listed.

Clean Water Act – Toxic Pollutants:

No component(s) listed.

DEA List I Chemicals (Precursor Chemicals):

No component(s) listed.

DEA List II Chemicals (Essential Chemicals):

No component(s) listed.

EPA List of Lists:313 Category Code:

71-36-3 BUTANOL

107-21-1 ETHANEDIOL

EPCRA 302 EHS TPQ:

No component(s) listed.

15. Regulatory information ... / >>

EPCRA 304 EHS RQ:
No component(s) listed.

CERCLA RQ:
71-36-3 BUTANOL
107-21-1 ETHANEDIOL

EPCRA 313 TRI:
71-36-3 BUTANOL
107-21-1 ETHANEDIOL

RCRA Code:
71-36-3 BUTANOL

CAA 112 (r) RMP TQ:
No component(s) listed.

State Regulations

Massachusetts:
71-36-3 BUTANOL
107-21-1 ETHANEDIOL

Minnesota:
71-36-3 BUTANOL
107-21-1 ETHANEDIOL

New Jersey:
71-36-3 BUTANOL
107-21-1 ETHANEDIOL

New York:
71-36-3 BUTANOL
107-21-1 ETHANEDIOL

Pennsylvania:
71-36-3 BUTANOL
107-21-1 ETHANEDIOL

California:
71-36-3 BUTANOL
107-21-1 ETHANEDIOL

Proposition 65:
WARNING! This product contains chemicals known to the State of California to cause cancer and birth defects or reproductive harm.
107-21-1 ETHANEDIOL D

International Regulations
Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:
None

Substances subject to the Rotterdam Convention:
None

Substances subject to the Stockholm Convention:
None

16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

H226	Flammable liquid and vapour.
H227	Combustible liquid.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.

16. Other information ... / >>**H336**
H400May cause drowsiness or dizziness.
Very toxic to aquatic life.**LEGEND:**

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAA 112 ® RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®)
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: EC Regulation 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh - Registry of Toxic Effects of Chemical Substances
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Communication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachusetts 105 CMR Department of public health 670.000: "Right to Know"
- Minnesota Chapter 5206 Department Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

16. Other information ... / >>

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Product classification derives from criteria established by the OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200), unless determined otherwise in Section 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified:

01 / 03 / 04 / 08 / 09 / 12 / 15.