

Safety Data Sheet acc. to OSHA HCS (HazCom 2012)

Printing date 08/14/2020

Reviewed on 08/14/2020

1 Identification

- **Product identifier**
- **Trade name:** Vario Molybdenum HR2 F10 / F25
- **Catalogue number:** 00530769, 00530799, 530760, 530790, 4530760, 4530790, 530762
- **Application of the substance / the mixture:** Reagent for water analysis
- **Manufacturer/Supplier:**
Tintometer Inc.
6456 Parkland Drive
Sarasota, FL 34243
USA
phone: (941) 756-6410
fax: (941) 727-9654
www.lovibond.us
Made in Germany
- **Emergency telephone number:** + 1 866 928 0789 (English, French, Spanish)

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**

· **GHS label elements** The product is classified and labeled according to the Hazard Communication Standard (HCS).

- **Hazard pictograms**



GHS07



GHS08

- **Signal word** Danger
- **Hazard-determining components of labeling:**
disodium peroxodisulphate
- **Hazard statements**
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
- **Precautionary statements**
P261 Avoid breathing dust.
P280 Wear protective gloves/protective clothing/eye protection.
P302+P352 If on skin: Wash with plenty of water.

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS (HazCom 2012)

Printing date 08/14/2020

Reviewed on 08/14/2020

Trade name: Vario Molybdenum HR2 F10 / F25

(Contd. of page 1)

- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- **Other hazards** No further relevant information available.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of inorganic compounds.
- **Composition and Information on Ingredients:**
Percent ranges are used due to the confidential product information.

CAS: 7757-82-6 EINECS: 231-820-9	sodium sulphate	60–70%
CAS: 7775-27-1 EINECS: 231-892-1 RTECS: SE0525000	disodium peroxodisulphate ⚠ Ox. Sol. 3, H272; ⚠ Resp. Sens. 1, H334; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	25–35%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

* 4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air or oxygen; call for doctor.
- **After skin contact:**
Immediately rinse with plenty of water.
If skin irritation or rash occurs: Get medical advice/attention.
- **After eye contact:** Rinse opened eye for several minutes (at least 15 min) under running water. Then consult a doctor.
- **After swallowing:**
Rinse out mouth and then drink 1-2 glasses of water.
Seek medical treatment.
- **Most important symptoms and effects, both acute and delayed**
allergic reactions
irritations
after inhalation:
mucosal irritations, cough, breathing difficulty
asthma attacks
after swallowing:
mucous membrane irritation
sickness
vomiting
gastric or intestinal disorders
cardiovascular disorders
- **Danger:**
Danger of impaired breathing.
Danger of pulmonary edema.
risk of airways sensitization
risk of skin sensitization
- **Indication of any immediate medical attention and special treatment needed:** No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture**
The product is not combustible.
Has a fire-promoting effect due to release of oxygen.
Formation of toxic gases is possible during heating or in case of fire.
Sulfur oxides (SO_x)
Oxygen (O₂)

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS (HazCom 2012)

Printing date 08/14/2020

Reviewed on 08/14/2020

Trade name: Vario Molybdenum HR2 F10 / F25

(Contd. of page 2)

Sodium oxide

· **Advice for firefighters**· **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

· **Additional information**

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Ambient fire may liberate hazardous vapours.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**· **Advice for non-emergency personnel:**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Avoid formation of dust.

· **Advice for emergency responders:** Protective equipment: see section 8· **Environmental precautions:** Do not allow product to reach sewage system or any water course.· **Methods and material for containment and cleaning up:**

Ensure adequate ventilation.

Pick up mechanically.

Dispose contaminated material as waste according to item 13.

· **Reference to other sections**

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

* 7 Handling and storage

· **Precautions for safe handling**· **Advice on safe handling:**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of dust.

Thorough dedusting.

· **Hygiene measures:**

Do not inhale dust / smoke / mist.

Avoid contact with the skin.

Avoid contact with the eyes.

Take off immediately all contaminated clothing.

Wash hands before breaks and at the end of work.

Do not eat, drink or smoke when using this product.

· **Conditions for safe storage, including any incompatibilities**· **Storage:**· **Requirements to be met by storerooms and receptacles:** Store in a cool location.· **Information about storage in one common storage facility:**

Store away from flammable substances.

Store away from reducing agents.

· **Further information about storage conditions:**

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Protect from exposure to the light.

Protect from humidity and water.

This product is hygroscopic.

· **Recommended storage temperature:** 20°C +/- 5°C (approx. 68°F)· **Specific end use(s)** No further relevant information available.

US —
(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS (HazCom 2012)

Printing date 08/14/2020

Reviewed on 08/14/2020

Trade name: Vario Molybdenum HR2 F10 / F25

(Contd. of page 3)

8 Exposure controls/personal protection

· Control parameters

· Components with limit values that require monitoring at the workplace:

CAS: 7757-82-6 sodium sulphate

TLV (USA)	Short-term value: NIC-0.2 mg/m ³ thoracic fraction of aerosol
-----------	---

CAS: 7775-27-1 disodium peroxodisulphate

TLV (USA)	Long-term value: 0.1 mg/m ³ as persulfate
-----------	---

EL (Canada)	Long-term value: 0.1 mg/m ³ as persulfate
-------------	---

EV (Canada)	Long-term value: 0.1 mg/m ³
-------------	--

· Additional information: The lists that were valid during the creation were used as basis.

· Engineering measures:

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment.
See item 7.

· Personal protective equipment:

· Breathing equipment: Use respiratory protective device against the effects of fume/dust/aerosol.

· Recommended filter device for short term use: Filter P2

· Protection of hands:

Protective gloves

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.11 mm

· Penetration time of glove material

Value for the permeation: Level ≤ 1 (10 min)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Safety glasses

· Body protection: Protective work clothing

· Limitation and supervision of exposure into the environment:

Do not allow product to reach sewage system or any water course.

* 9 Physical and chemical properties

· Information on basic physical and chemical properties

· Appearance:

Form / Physical state:	Powder
Color:	White

· Odor:	Odorless
---------	----------

· Odor threshold:	Not applicable.
-------------------	-----------------

· pH-value (10.8 g/l) at 20°C (68°F):	5.6
---------------------------------------	-----

· Melting point/freezing point:	Not determined.
---------------------------------	-----------------

· Initial boiling point and boiling range:	Not applicable. Decomposition
--	----------------------------------

· Flash point:	Not applicable.
----------------	-----------------

· Flammability (solid, gas):	The product is not combustible.
------------------------------	---------------------------------

· Decomposition temperature:	> 180°C (> 356°F) (CAS 7775-27-1)
------------------------------	-----------------------------------

· Auto-ignition temperature:	Product is not self-igniting.
------------------------------	-------------------------------

· Danger of explosion:	Product does not present an explosion hazard. As the product is supplied it is not capable of dust explosion; however enrichment with fine dust causes risk of dust explosion.
------------------------	---

(Contd. on page 5)

US

Safety Data Sheet

acc. to OSHA HCS (HazCom 2012)

Printing date 08/14/2020

Reviewed on 08/14/2020

Trade name: Vario Molybdenum HR2 F10 / F25

(Contd. of page 4)

· Flammability or explosive limits:	
Lower:	Not determined.
Upper:	Not determined.
· Oxidizing properties:	Oxidizing potential CAS 7775-27-1: is classified as oxidizing.
· Vapor Pressure:	Not applicable.
· Density at 20°C (68°F):	2.32 g/cm ³ (19.36 lbs/gal)
· Relative density:	Not determined.
· Vapor density:	Not applicable.
· Evaporation rate:	Not applicable.
· Solubility(ies)	
Water:	Soluble.
· Partition coefficient (n-octanol/water):	Not applicable.
· Viscosity:	Not applicable.
· Solvent content:	
Solids content:	100.0 %
· Other information	No further relevant information available.

*10 Stability and reactivity

- **Reactivity** Dust can combine with air to form an explosive mixture.
- **Chemical stability** Stable at ambient temperature (room temperature).
- **Possibility of hazardous reactions**
 - Reacts with reducing agents.
 - Reacts with alcohols.
 - Reacts with strong acids and alkali.
 - Reacts with heavy metals.
- **Conditions to avoid**
 - Exposure to moisture.
 - Strong heating (decomposition)
- **Incompatible materials:**
 - combustible materials
 - aluminum
- **Hazardous decomposition products:**
 - oxygen
 - In case of fire: see section 5.

*11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:** Based on available data, the classification criteria are not met.

· **Acute toxicity estimate (ATE_(MIX)) - Calculation method:**

Oral	GHS ATE _(MIX)	2629 mg/kg (.)
------	--------------------------	----------------

· **LD/LC50 values that are relevant for classification:**

The following statements refer to the individual components.

CAS: 7757-82-6 sodium sulphate

Oral	LD50.	>2000 mg/kg (rat) (OECD 423) (Registrant, ECHA, limit test)
Dermal	LD50.	>2000 mg/kg (rat)
Inhalative	LC50.	>2.4 mg/l/4h (rat) (OECD 436) (Registrant, ECHA: all animals survived at these concentration - the highest producible concentration)

CAS: 7775-27-1 disodium peroxodisulphate

Oral	LD50	920 mg/kg (rat) (IUCLID)
------	------	-----------------------------

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS (HazCom 2012)

Printing date 08/14/2020

Reviewed on 08/14/2020

Trade name: Vario Molybdenum HR2 F10 / F25

(Contd. of page 5)

Dermal	LD50	>10000 mg/kg (rabbit)
Inhalative	LC50.	>5.1 mg/l/4h (rat) (ECHA: no deaths at this concentration LC ₅₀ = >5.1)
	LD50 IPR	226 mg/kg (mouse)

- **Primary irritant effect:**
- **on the skin:** Causes skin irritation.
- **on the eye:** Causes serious eye irritation.

· Information on components:

CAS: 7757-82-6 sodium sulphate

Irritation of skin	OECD 404	(rabbit: no irritation)
Irritation of eyes	OECD 405	(rabbit: slight irritation)

CAS: 7775-27-1 disodium peroxodisulphate

Irritation of skin	OECD 404	(rabbit: slight irritation) (ECHA: read-across CAS 7727-54-0 Diammonium persulfate)
Irritation of eyes	OECD 405	(rabbit: slight irritation) (ECHA: read-across CAS 7727-54-0 Diammonium persulfate)

· Sensitization:

May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.

· Information on components:

CAS: 7757-82-6 sodium sulphate

Sensitization	OECD 406	(guinea pig: negative)
---------------	----------	------------------------

CAS: 7775-27-1 disodium peroxodisulphate

Sensitization	OECD 406	(guinea pig: positive)
---------------	----------	------------------------

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

· Other information: see section 8 / 15

· Synergistic Products: None

· CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction): The following statements refer to the mixture:

- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT (specific target organ toxicity) -single exposure** May cause respiratory irritation.
- **STOT (specific target organ toxicity) -repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

· Information on components:

OECD 414: Teratogenicity testing
OECD 473: Mutagenicity testing
OECD 471, 474, 476, 487: Germ cell mutagenicity testing

CAS: 7775-27-1 disodium peroxodisulphate

OECD 471	(negative) (Bacterial Reverse Mutation Test - Ames test) (IUCLID)
----------	--

· Additional toxicological information: Other dangerous properties can not be excluded.

Safety Data Sheet

acc. to OSHA HCS (HazCom 2012)

Printing date 08/14/2020

Reviewed on 08/14/2020

Trade name: Vario Molybdenum HR2 F10 / F25

(Contd. of page 6)

12 Ecological information

· Toxicity

· Aquatic toxicity:

CAS: 7757-82-6 sodium sulphate

EC50	2564 mg/l/48h (Daphnia magna) (IUCLID)
LC50	120 mg/l/96h (mosquitofish) (IUCLID)
	13500–14500 mg/l/96h (fathhead minnow)

CAS: 7775-27-1 disodium peroxodisulphate

EC50	133 mg/l/48h (Daphnia magna)
NOEC	91.7 mg/l/96h (rainbow trout) (ECHA)
NOEC	67.6 mg/l/48 h (Daphnia magna) (ECHA)
LC50	771 mg/l/96h (bluegill)
	163 mg/l/96h (rainbow trout) (ECHA)

· Bacterial toxicity:

sulfates toxic > 2.5 g/l

CAS: 7757-82-6 sodium sulphate

EC10	>1000 mg/l (Pseudomonas putida) (16h) (IUCLID)
------	---

· Other information:

Toxic for fish:
sulfates > 7 g/l

· Persistence and degradability .

· Other information:

Mixture of inorganic compounds.
Methods for the determination of biodegradability are not applicable to inorganic substances.

· Bioaccumulative potential

No further relevant information available.

· Mobility in soil

No further relevant information available.

· Other adverse effects

Reacts with water to form toxic decomposition products.

Avoid transfer into the environment.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
Hand over to hazardous waste disposers.

· Uncleaned packagings:

· Recommendation:

Disposal must be made according to official regulations.

· Recommended cleansing agent:

Water, if necessary with cleansing agents.

14 Transport information

· UN-Number

DOT, IMDG, IATA none

· UN proper shipping name

DOT, IMDG, IATA none

· Transport hazard class(es)

DOT, IMDG, IATA
Class none

(Contd. on page 8)

US

Safety Data Sheet

acc. to OSHA HCS (HazCom 2012)

Printing date 08/14/2020

Reviewed on 08/14/2020

Trade name: Vario Molybdenum HR2 F10 / F25

(Contd. of page 7)

· Packing group	
· DOT, IMDG, IATA	none
· Environmental hazards:	Not applicable.
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	Not dangerous according to the above specifications.

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture
· Sara
· Section 355 (Extremely hazardous substances):
None of the ingredients is listed.
· Section 313 (Specific toxic chemical listings):
None of the ingredients is listed.
· TSCA (Toxic Substances Control Act):
All components have the value ACTIVE.
· Hazardous Air Pollutants
None of the ingredients is listed.
· Proposition 65
· Chemicals known to cause cancer:
None of the ingredients is listed.
· Chemicals known to cause reproductive toxicity for females:
None of the ingredients is listed.
· Chemicals known to cause reproductive toxicity for males:
None of the ingredients is listed.
· Chemicals known to cause developmental toxicity:
None of the ingredients is listed.
· New Jersey Right-to-Know List:
CAS: 7775-27-1 disodium peroxodisulphate
· New Jersey Special Hazardous Substance List:
None of the ingredients is listed.
· Pennsylvania Right-to-Know List:
CAS: 7757-82-6 sodium sulphate
· Pennsylvania Special Hazardous Substance List:
CAS: 7757-82-6 sodium sulphate
E
· EPA (Environmental Protection Agency)
None of the ingredients is listed.
· NIOSH-Ca (National Institute for Occupational Safety and Health)
None of the ingredients is listed.
· Information about limitation of use: Employment restrictions concerning young persons must be observed.
· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

*16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
- H272 May intensify fire; oxidizer.

(Contd. on page 9)

US

Safety Data Sheet

acc. to OSHA HCS (HazCom 2012)

Printing date 08/14/2020

Reviewed on 08/14/2020

Trade name: Vario Molybdenum HR2 F10 / F25

(Contd. of page 8)

H302 Harmful if swallowed.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H335 May cause respiratory irritation.

• **Date of preparation / last revision** 08/14/2020 / 36

• **Abbreviations and acronyms:**

OECD: Organisation for Economic Co-operation and Development
 STOT: specific target organ toxicity
 SE: single exposure
 RE: repeated exposure
 EC50: half maximal effective concentration
 IC50: half maximal inhibitory concentration
 NOEL or NOEC: No Observed Effect Level or Concentration
 ACGIH® - American Conference of Governmental Industrial Hygienists
 •A1 - Confirmed human carcinogen
 •A2 - Suspected human carcinogen
 •A3 - Confirmed animal carcinogen with unknown relevance to humans
 •A4 - Not classifiable as a human carcinogen
 •A5 - Not suspected as a human carcinogen
 IARC - International Agency for Research on Cancer
 •Group 1 - Carcinogenic to humans
 •Group 2A - Probably carcinogenic to humans
 •Group 2B - Possibly carcinogenic to humans
 •Group 3 - Not classifiable as to carcinogenicity to humans
 •Group 4 - Probably not carcinogenic to humans
 NTP - National Toxicology Program, U.S. Department of Health and Human Services
 •Group K - Known to be Human Carcinogens
 •Group R - Reasonably Anticipated to be Human Carcinogens
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 Ox. Sol. 3: Oxidizing solids – Category 3
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
 Resp. Sens. 1: Respiratory sensitisation – Category 1
 Skin Sens. 1: Skin sensitisation – Category 1
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

• **Sources**

Data arise from safety data sheets, reference works and literature.
 ECHA: European CHemicals Agency <http://echa.europa.eu>
 IUCLID (International Uniform Chemical Information Database)

• *** Data compared to the previous version altered.**

— US —