

SECTION 1: Identification

1.1. Identification

Product form : Mixtures
Product name : Sulfuric Acid, 5.0N (2.5M)
Product code : LC25840

1.2. Recommended use and restrictions on use

Use of the substance/mixture : For laboratory and manufacturing use only.
Recommended use : Laboratory chemicals
Restrictions on use : Not for food, drug or household use

1.3. Supplier

LabChem Inc
Jackson's Pointe Commerce Park Building 1000, 1010 Jackson's Pointe Court
Zelienople, PA 16063 - USA
T 412-826-5230 - F 724-473-0647
info@labchem.com - www.labchem.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 or 011-703-527-3887

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin corrosion/irritation H314 Causes severe skin burns and eye damage
Category 1B
Serious eye damage/eye irritation Category 1 H318 Causes serious eye damage
Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS05

Signal word (GHS-US) : Danger
Hazard statements (GHS-US) : H314 - Causes severe skin burns and eye damage
Precautionary statements (GHS-US) : P260 - Do not breathe mist, vapors, spray
P264 - Wash exposed skin thoroughly after handling
P280 - Wear protective gloves, protective clothing, eye protection, face protection
P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a poison center or doctor/physician
P363 - Wash contaminated clothing before reuse
P405 - Store locked up
P501 - Dispose of contents/container to comply with local, state and federal regulations
If inhaled: Remove person to fresh air and keep comfortable for breathing

2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification : None.

2.4. Unknown acute toxicity (GHS US)

Not applicable

Sulfuric Acid, 5.0N (2.5M)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Water	(CAS-No.) 7732-18-5	78.69	Not classified
Sulfuric Acid	(CAS-No.) 7664-93-9	21.31	Skin Corr. 1A, H314 Eye Dam. 1, H318

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.
- First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a poison center or doctor/physician.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects : Causes severe skin burns and eye damage.
- Symptoms/effects after eye contact : Causes serious eye damage.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

- Reactivity : Thermal decomposition generates : Corrosive vapors.

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Protective equipment : Safety glasses. Gloves. Protective clothing. Head/neck protection.
- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

Sulfuric Acid, 5.0N (2.5M)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not breathe mist, vapors, spray. Avoid contact during pregnancy/while nursing.
- Hygiene measures : Wash exposed skin thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations.
- Storage conditions : Keep only in the original container in a cool, well ventilated place away from : incompatible materials. Keep container closed when not in use.
- Incompatible products : Strong bases. metals. cyanides.
- Incompatible materials : Heat sources.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Sulfuric Acid (7664-93-9)		
ACGIH	ACGIH TWA (mg/m ³)	0.2 mg/m ³ (Sulfuric acid; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Thoracic fraction)
OSHA	OSHA PEL (TWA) (mg/m ³)	1 mg/m ³
IDLH	US IDLH (mg/m ³)	15 mg/m ³
NIOSH	NIOSH REL (TWA) (mg/m ³)	1 mg/m ³
Water (7732-18-5)		
Not applicable		

8.2. Appropriate engineering controls

- Appropriate engineering controls : Emergency eye wash fountains should be available in the immediate vicinity of any potential exposure. Provide adequate general and local exhaust ventilation.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Chemical resistant apron. Face shield. Gloves. Safety glasses. Protective clothing.



Hand protection:

Wear protective gloves

Eye protection:

Chemical goggles or face shield

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear appropriate mask

Other information:

Do not eat, drink or smoke during use.

Sulfuric Acid, 5.0N (2.5M)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear, colorless liquid.
Color	: Colorless
Odor	: None.
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 1.15 g/ml
Solubility	: Soluble in water.
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 1.38 cSt
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: Not applicable.
Oxidizing properties	: None.

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Thermal decomposition generates : Corrosive vapors.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reacts violently with (some) bases: release of heat.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

metals. Strong bases. cyanides.

10.6. Hazardous decomposition products

Sulfur compounds. Thermal decomposition generates : Corrosive vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure	: Skin and eye contact
Acute toxicity	: Not classified

Sulfuric Acid (7664-93-9)

LD50 oral rat	2140 mg/kg body weight (Rat; Experimental value)
---------------	--

Sulfuric Acid, 5.0N (2.5M)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Sulfuric Acid (7664-93-9)	
ATE US (oral)	2140 mg/kg body weight
Water (7732-18-5)	
LD50 oral rat	≥ 90000 mg/kg
ATE US (oral)	90000 mg/kg body weight

Skin corrosion/irritation	: Causes severe skin burns and eye damage.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Sulfuric Acid (7664-93-9)	
Additional information	Strong inorganic acid mists containing sulfuric acid are carcinogenic to humans
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	2 - Known Human Carcinogens

Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/effects after eye contact	: Causes serious eye damage.

SECTION 12: Ecological information

12.1. Toxicity

Sulfuric Acid (7664-93-9)	
LC50 fish 1	42 mg/l (LC50; 96 h)
EC50 Daphnia 1	29 mg/l (EC50; 24 h)

12.2. Persistence and degradability

Sulfuric Acid, 5.0N (2.5M)	
Persistence and degradability	Not established.
Sulfuric Acid (7664-93-9)	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
Water (7732-18-5)	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Sulfuric Acid, 5.0N (2.5M)	
Bioaccumulative potential	Not established.
Sulfuric Acid (7664-93-9)	
Log Pow	-2.2 (Estimated value)
Bioaccumulative potential	Bioaccumulation: not applicable.
Water (7732-18-5)	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

No additional information available

Sulfuric Acid, 5.0N (2.5M)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.5. Other adverse effects

Effect on the global warming	: No known effects from this product.
GWPmix comment	: No known effects from this product.
Other information	: Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to comply with local, state and federal regulations.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description	: UN2796 Sulfuric acid (with not more than 51% acid), 8, II
UN-No.(DOT)	: UN2796
Proper Shipping Name (DOT)	: Sulfuric acid with not more than 51% acid
Transport hazard class(es) (DOT)	: 8 - Class 8 - Corrosive material 49 CFR 173.136
Packing group (DOT)	: II - Medium Danger
Hazard labels (DOT)	: 8 - Corrosive



DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Special Provisions (49 CFR 172.102)	: A3 - For combination packaging, if glass inner packaging (including ampoules) are used, they must be packed with absorbent material in tightly closed metal receptacles before packing in outer packaging. A7 - Steel packaging must be corrosion-resistant or have protection against corrosion. B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized. B15 - Packaging must be protected with non-metallic linings impervious to the lading or have a suitable corrosion allowance. IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. N6 - Battery fluid packaged with electric storage batteries, wet or dry, must conform to the packaging provisions of 173.159 (g) or (h) of this subchapter. N34 - Aluminum construction materials are not authorized for any part of a packaging which is normally in contact with the hazardous material. T8 - 4 178.274(d)(2) Normal..... Prohibited TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively. TP12 - This material is considered highly corrosive to steel.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 154
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 1 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 30 L

Sulfuric Acid, 5.0N (2.5M)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
Other information	: No supplementary information available.

SECTION 15: Regulatory information

15.1. US Federal regulations

Sulfuric Acid, 5.0N (2.5M)

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
-------------------------------------	---------------------------------

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Sulfuric Acid, ACS	CAS-No. 7664-93-9	21.31%
--------------------	-------------------	--------

Sulfuric Acid (7664-93-9)

RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	1000 lb
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

Sulfuric Acid (7664-93-9)

Listed on IARC (International Agency for Research on Cancer)
Listed as carcinogen on NTP (National Toxicology Program)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information


Revision date : 07/26/2017

Other information : None.

Full text of H-phrases: see section 16:

H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage

NFPA health hazard	: 3 - Materials that, under emergency conditions, can cause serious or permanent injury.
NFPA fire hazard	: 0 - Materials that will not burn under typical dire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand.
NFPA reactivity	: 0 - Material that in themselves are normally stable, even under fire conditions.



Sulfuric Acid, 5.0N (2.5M)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability : 0 Minimal Hazard - Materials that will not burn

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal protection : H

H - Splash goggles, Gloves, Synthetic apron, Vapor respirator

SDS US LabChem

Information in this SDS is from available published sources and is believed to be accurate. No warranty, express or implied, is made and LabChem Inc assumes no liability resulting from the use of this SDS. The user must determine suitability of this information for his application.