

1. Identification

Product identifier	ALCOHOL, REAGENT (ACS)	
Other means of identification		
Product code	1850	
Synonyms	REAGENT ALCOHOL * ETHYL ALCOHOL * ETHANOL * DENATURED ALCOHOL	
Recommended use	solvent technical function of substance professional, scientific and technical activities: other professional, scientific and technical activities	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/Distributor information		
Manufacturer		
Company name	GFS Chemicals, Inc.	
Address	P.O. Box 245 Powell, OH 43065 United States	
Telephone	Phone	740-881-5501
	Toll Free	800-858-9682
	Fax	740-881-5989
Website	www.gfschemicals.com	
E-mail	service@gfschemicals.com	
Emergency phone number	Emergency Assistance	Chemtrec 800-424-9300

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 2
Health hazards	Serious eye damage/eye irritation	Category 2A
	Sensitization, respiratory	Category 1
	Germ cell mutagenicity	Category 1B
	Reproductive toxicity	Category 1A
	Specific target organ toxicity, single exposure	Category 1 (central nervous system, kidney, systemic toxicity)
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
Environmental hazards	Specific target organ toxicity, repeated exposure	Category 1 (central nervous system, liver, visual organs)
	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 2
OSHA defined hazards	Not classified.	
Label elements		



Signal word Danger

Hazard statement Highly flammable liquid and vapor. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. May cause genetic defects. May damage fertility or the unborn child. Causes damage to organs (central nervous system, kidney, systemic toxicity). Causes damage to organs (central nervous system, liver, visual organs) through prolonged or repeated exposure. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation wear respiratory protection.

Response

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. In case of fire: Use appropriate media for extinction. Eliminate all ignition sources if safe to do so.

Storage

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

Disposal

Dispose of contents/container to an approved incineration plant.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ETHYL ALCOHOL	ABSOLUTE ETHANOL	64-17-5	90
ISOPROPYL ALCOHOL	ISOPROPANOL 2-PROPANOL	67-63-0	5
METHYL ALCOHOL	WOOD ALCOHOL METHANOL	67-56-1	5

Constituents

Common name and synonyms

CAS number

%

Chemical name

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.

Eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. If ingestion of a large amount does occur, call a poison control center immediately.

Most important symptoms/effects, acute and delayed

Irritation of eyes and mucous membranes. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Narcosis. Decrease in motor functions. Behavioral changes. Edema. Liver enlargement. Jaundice. Proteinuria. May cause allergic respiratory reaction. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Symptoms may be delayed. Provide general supportive measures and treat symptomatically.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Carbon dioxide (CO₂). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only. Alcohol resistant foam. Powder.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical	This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. By heating and fire, harmful vapors/gases may be formed. Material will float and may ignite on surface of water.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Water runoff can cause environmental damage.
Specific methods	In the event of fire and/or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk.
General fire hazards	Highly flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak. Keep upwind. Keep out of low areas. Ventilate closed spaces before entering them. Avoid inhalation of vapors or mists. Wear appropriate personal protective equipment.
Methods and materials for containment and cleaning up	ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Should not be released into the environment. This product is miscible in water. Large Spills: Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. This material and its container must be disposed of as hazardous waste. Following product recovery, flush area with water. Clean up in accordance with all applicable regulations. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.
Environmental precautions	Never return spills in original containers for re-use. For waste disposal, see section 13 of the SDS. Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground. Avoid release to the environment. Use appropriate containment to avoid environmental contamination. Prevent further leakage or spillage if safe to do so. Do not contaminate water.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Vapors may form explosive mixtures with air. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code". DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid contact with eyes. Avoid contact during pregnancy/while nursing. Use personal protective equipment as required. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Avoid release to the environment. Do not empty into drains.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in cool place. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a well-ventilated place. Keep container tightly closed. Keep in an area equipped with sprinklers. Keep out of the reach of children. Store in a cool, dry place out of direct sunlight.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
ETHYL ALCOHOL (CAS 64-17-5)	PEL	1900 mg/m3
ISOPROPYL ALCOHOL (CAS 67-63-0)	PEL	1000 ppm 980 mg/m3
METHYL ALCOHOL (CAS 67-56-1)	PEL	400 ppm 260 mg/m3
		200 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
ETHYL ALCOHOL (CAS 64-17-5)	STEL	1000 ppm
ISOPROPYL ALCOHOL (CAS 67-63-0)	STEL	400 ppm
METHYL ALCOHOL (CAS 67-56-1)	TWA	200 ppm
	STEL	250 ppm
	TWA	200 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
ETHYL ALCOHOL (CAS 64-17-5)	TWA	1900 mg/m3
ISOPROPYL ALCOHOL (CAS 67-63-0)	STEL	1000 ppm 1225 mg/m3
	TWA	500 ppm 980 mg/m3 400 ppm
METHYL ALCOHOL (CAS 67-56-1)	STEL	325 mg/m3
	TWA	250 ppm 260 mg/m3 200 ppm

Biological limit values

US. ACGIH. BEIs. Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
ISOPROPYL ALCOHOL (CAS 67-63-0)	40 mg/l	Acetone	Urine	*
METHYL ALCOHOL (CAS 67-56-1)	15 mg/l	Methanol	Urine	*

* - For sampling details, please see the source document.

Exposure guidelines

US - Tennessee OELs: Skin designation

METHYL ALCOHOL (CAS 67-56-1) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

METHYL ALCOHOL (CAS 67-56-1) Can be absorbed through the skin.

US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants

METHYL ALCOHOL; METHANOL (CAS 67-56-1) Can be absorbed through the skin.

US. Minnesota Hazardous Substances List (Minn. Rules 5206.0400).

METHYL ALCOHOL (CAS 67-56-1) Skin designation applies.

US. NIOSH: Pocket Guide to Chemical Hazards

METHYL ALCOHOL (CAS 67-56-1) Can be absorbed through the skin.

Appropriate engineering controls Explosion-proof general and local exhaust ventilation. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear chemical goggles.

Skin protection

Hand protection Wear protective gloves.

Other Wear appropriate chemical resistant clothing. Wear protective gloves.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with organic vapor cartridge.

Thermal hazards Not available.

General hygiene considerations When using, do not eat, drink or smoke. Avoid contact with eyes. Wash hands before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Appearance	Clear.
Physical state	Liquid.
Form	Liquid.
Color	Colorless.
Odor	Alcoholic.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	-169.61 °F (-112.01 °C) estimated
Initial boiling point and boiling range	172.4 °F (78 °C)
Flash point	55.4 °F (13.0 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	3.5 % estimated
Flammability limit - upper (%)	24 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	82.65 hPa estimated

Vapor density	1.6
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Miscible.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	677.21 °F (358.45 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	0.79 g/cm3
Flammability class	Flammable IB estimated
Flash point class	Flammable IB
Percent volatile	100 %
Specific gravity	0.79
VOC (Weight %)	100 % estimated

10. Stability and reactivity

Reactivity	Not available.
Chemical stability	Risk of explosion. Stable at normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Heat, flames and sparks. Avoid temperatures exceeding the flash point.
Incompatible materials	Oxidizing materials. Strong oxidizing agents. Isocyanates. Acids. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause irritation to the respiratory system. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin contact	Due to lack of data the classification is not possible.
Eye contact	Causes serious eye irritation.
Ingestion	Based on available data, the classification criteria are not met.
Symptoms related to the physical, chemical and toxicological characteristics	Narcosis. Edema. Liver enlargement. Jaundice. Proteinuria. Behavioral changes. Decrease in motor functions. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Information on toxicological effects

Acute toxicity

Product	Species	Test Results
ALCOHOL, REAGENT		
Acute		
Dermal		
LD50	Rabbit	99999 mg/kg
Inhalation		
LC50	Cat	1708 mg/l, 4.5 Hours estimated 874 mg/l, 6 Hours estimated
	Mouse	43 mg/l, 4 Hours estimated
	Rat	22222 ppm, 10 Hours estimated 1750 mg/l, 6 Hours estimated
Oral		
LD50	Dog	95940 mg/kg 6.1 g/kg estimated
	Guinea pig	6.2 g/kg estimated

Product	Species	Test Results
Other LD50	Monkey	40 g/kg estimated
	Mouse	72000 mg/kg
	Rabbit	99999 mg/kg
		75 g/kg estimated
	Rat	7060 mg/kg
		5628 mg/kg
	Mouse	30180 mg/kg
Components	Species	Test Results
ETHYL ALCOHOL (CAS 64-17-5)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	39 mg/l, 4 Hours
	Rat	20000 ppm, 10 Hours
Oral		
LD50	Dog	5.5 g/kg
	Guinea pig	5.6 g/kg
	Mouse	3450 mg/kg
	Rat	7060 mg/kg
		6.2 g/kg
Other		
LD50	Mouse	933 mg/kg
	Rat	1440 mg/kg
ISOPROPYL ALCOHOL (CAS 67-63-0)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	5030 - 7900 mg/kg
		12800 mg/kg
Oral		
LD50	Dog	4797 mg/kg
	Mouse	3600 mg/kg
		4.5 g/kg
	Rabbit	8000 mg/kg
		6410 mg/kg
		5.03 g/kg
	Rat	4700 - 5800 mg/kg
		5045 mg/kg
		4.7 g/kg
Other		
LD50	Mouse	1509 mg/kg
	Rat	1099 mg/kg
METHYL ALCOHOL (CAS 67-56-1)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	15800 mg/kg
Inhalation		
LC50	Cat	85.41 mg/l, 4.5 Hours
		43.68 mg/l, 6 Hours
	Rat	64000 mg/l, 4 Hours

Components	Species	Test Results
		87.5 mg/l, 6 Hours
Oral		
LD50	Dog	8000 mg/kg
	Monkey	2 g/kg
	Mouse	7300 mg/kg
	Rabbit	14.4 g/kg
	Rat	5628 mg/kg
Other		
LD50	Guinea pig	3556 mg/kg
	Hamster	8555 mg/kg
	Monkey	3 g/kg
	Mouse	4100 mg/kg
	Rabbit	1826 mg/kg
	Rat	2131 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Due to lack of data the classification is not possible.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin sensitization Due to lack of data the classification is not possible.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

US OSHA Hazard Categories (1)

Not regulated.

US OSHA Hazard Categories (10)

Not regulated.

US OSHA Hazard Categories (2)

Not regulated.

US OSHA Hazard Categories (3)

Not regulated.

US OSHA Hazard Categories (4)

Not regulated.

US OSHA Hazard Categories (5)

Not regulated.

US OSHA Hazard Categories (6)

Not regulated.

US OSHA Hazard Categories (7)

Not regulated.

US OSHA Hazard Categories (8)

Not regulated.

US OSHA Hazard Categories (9)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity Possible reproductive hazard. May damage fertility or the unborn child.

Specific target organ toxicity - single exposure Respiratory tract irritation. Narcotic effects. Causes damage to organs (central nervous system, kidney, systemic toxicity).

Specific target organ toxicity - repeated exposure Causes damage to organs (central nervous system, liver, visual organs) through prolonged or repeated exposure.

Aspiration hazard Due to lack of data the classification is not possible.

Chronic effects

Prolonged inhalation may be harmful. Causes damage to organs through prolonged or repeated exposure.

12. Ecological information**Ecotoxicity**

Toxic to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected. Contains a substance which causes risk of hazardous effects to the environment.

Product			Species	Test Results
ALCOHOL, REAGENT				
Aquatic				
Crustacea	EC50	Daphnia	5525.1104 mg/l, 48 hours estimated	
Fish	LC50	Fish	9967.9453 mg/l, 96 hours estimated	
Components			Species	Test Results
ETHYL ALCOHOL (CAS 64-17-5)				
Aquatic				
Crustacea	EC50	Water flea (Daphnia magna)	7.7 - 11.2 mg/l, 48 hours	
Fish	LC50	Fathead minnow (Pimephales promelas)	> 100 mg/l, 96 hours	
ISOPROPYL ALCOHOL (CAS 67-63-0)				
Aquatic				
Fish	LC50	Bluegill (Lepomis macrochirus)	> 1400 mg/l, 96 hours	
METHYL ALCOHOL (CAS 67-56-1)				
Aquatic				
Crustacea	EC50	Water flea (Daphnia magna)	> 10000 mg/l, 48 hours	
Fish	LC50	Fathead minnow (Pimephales promelas)	> 100 mg/l, 96 hours	

* Estimates for product may be based on additional component data not shown.

Persistence and degradability None known.

Bioaccumulative potential Not available.

Partition coefficient n-octanol / water (log Kow)

ETHYL ALCOHOL	-0.31
ISOPROPYL ALCOHOL	0.05
METHYL ALCOHOL	-0.77

Mobility in soil Not available.

Other adverse effects Not available.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazardous waste code	D001: Waste Flammable material with a flash point <140 F
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information**DOT**

UN number	UN1987
UN proper shipping name	Alcohols, n.o.s.
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II

Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	172, IB2, T7, TP1, TP8, TP28
Packaging exceptions	4b, 150
Packaging non bulk	202
Packaging bulk	242

IATA

UN number	UN1987
UN proper shipping name	Alcohols, n.o.s. (ETHYL ALCOHOL, ISOPROPYL ALCOHOL)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	No.
ERG Code	3L
Special precautions for user	Not available.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

UN number	UN1987
UN proper shipping name	ALCOHOLS, N.O.S., MARINE POLLUTANT
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	
Marine pollutant	Yes
EmS	F-E, S-D
Special precautions for user	Not available.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not available.


DOT



IATA; IMDG



Marine pollutant



General information

DOT Regulated Marine Pollutant. IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

METHYL ALCOHOL (CAS 67-56-1)

Listed.

SARA 304 Emergency release notification

Not regulated.

US OSHA Hazard Categories (1)

Not regulated.

US OSHA Hazard Categories (2)

Not regulated.

US OSHA Hazard Categories (3)

Not regulated.

US OSHA Hazard Categories (4)

Not regulated.

US OSHA Hazard Categories (5)

Not regulated.

US OSHA Hazard Categories (6)

Not regulated.

US OSHA Hazard Categories (7)

Not regulated.

US OSHA Hazard Categories (8)

Not regulated.

US OSHA Hazard Categories (9)

Not regulated.

US OSHA Hazard Categories (10)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes

Delayed Hazard - Yes

Fire Hazard - Yes

Pressure Hazard - No

Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312

No

Hazardous chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
METHYL ALCOHOL	67-56-1	5

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

METHYL ALCOHOL (CAS 67-56-1)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

ETHYL ALCOHOL (CAS 64-17-5)

Low priority

ISOPROPYL ALCOHOL (CAS 67-63-0)

Low priority

US state regulations

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

ISOPROPYL ALCOHOL (CAS 67-63-0)

METHYL ALCOHOL (CAS 67-56-1)

US. Massachusetts RTK - Substance List

ETHYL ALCOHOL (CAS 64-17-5)

ISOPROPYL ALCOHOL (CAS 67-63-0)

METHYL ALCOHOL (CAS 67-56-1)

US. New Jersey Worker and Community Right-to-Know Act

ETHYL ALCOHOL (CAS 64-17-5)

ISOPROPYL ALCOHOL (CAS 67-63-0)

METHYL ALCOHOL (CAS 67-56-1)

US. Pennsylvania Worker and Community Right-to-Know Law

ETHYL ALCOHOL (CAS 64-17-5)

ISOPROPYL ALCOHOL (CAS 67-63-0)

METHYL ALCOHOL (CAS 67-56-1)

US. Rhode Island RTK

ISOPROPYL ALCOHOL (CAS 67-63-0)

METHYL ALCOHOL (CAS 67-56-1)

US. California Proposition 65**US - California Proposition 65 - CRT: Listed date/Developmental toxin**

METHYL ALCOHOL (CAS 67-56-1)

Listed: March 16, 2012

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision**Issue date**

May-07-2014

Revision date

March-16-2016

Version #

02

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information

Hazard(s) identification: Response
Physical & Chemical Properties: Multiple Properties
Transport Information: Proper Shipping Name/Packing Group